



## LED Poster

**INDOOR**

### EYETOUCH

#### Features:

- Compact integration, multiple installation.
- Plug & play operation.
- Wireless fidelity connection, mobile app control (Android & IOS).
- Surface protective cover design, not reflective.
- Live editing, upload and show.
- Cluster control technology.
- Ultra light & thin.
- CE, ETL approval.



#### Specification:

Model	EYE TOUCH	Refresh Rate	1200-1920 Hz
Dimensions(WxHxD)	500x1926x56 mm / 19.69x75.83x2.20 inch	Best Viewing Distance	3~ 10m
Pixel Pitch	2.9mm / 0.11 inch	Viewing Angle(Horizontal)	130 (-65 ~ +65)°
Pixel Configuration	3 Chips in 1 SMD LED	Viewing Angle(Vertical)	130 (-65 ~ +65)°
Pixel Density	113,462 pixels/m <sup>2</sup>	Serviceability	Rear
Resolution(WxH)	160x640	Input Voltage	AC110-240V, 50 & 60Hz
Aspect ratio	1:4	Certifications	CE, ETL
Contrast Ratio	2000:1	Control Method	WIFI
Brightness	1200 nits(cd/m <sup>2</sup> )	Installation Method	standby, hung, wall mount, window design
Weight	25 kg / 55.12 lbs	Application Area	show, shopping mall, shop, reception, etc.

**Call us for details:**

#### Main Office:

722-8843 • 725-5424 • 724-7813  
721-4332 • 725-0437 • 727-0637  
721-6145 • 725-9359 • 722-8845

#### Showroom:

3rd Flr. V-Mall Shopping Ctr, Greenhills, San Juan City

#### The Brain Audiovisual Co.

5th Flr. Bldg B, SM Megamall, Mandaluyong City

**AV SALES  
RENTALS • DESIGN  
SYSTEM  
INTEGRATION**





## LED Poster

**INDOOR**

EYESIGN

### Features:

- Compact integration, multiple installation.
- Plug & play operation.
- Wireless fidelity connection, mobile app control (Android & IOS).
- Surface protective cover design, not reflective.
- Live editing, upload and show.
- Cluster control technology.
- Ultra light & thin.
- CE, EMC approval.



### Specification:

Model	EYESIGN	Refresh Rate	1200-1920 Hz
Dimensions(WxHxD)	840x2150x80mm /33.07x84.65x3.15 inch	Best Viewing Distance	3~ 10m
Pixel Pitch	2.9mm / 0.11 inch	Viewing Angle(Horizontal)	130 (-65 ~ +65)°
Pixel Configuration	3 Chips in 1 SMD LED	Viewing Angle(Vertical)	130 (-65~ +65)°
Pixel Density	113,462 pixels/m <sup>2</sup>	Serviceability	Rear
Resolution(WxH)	256x640	Input Voltage	AC110-240V, 50 & 60Hz
Aspect ratio	2:5	Certifications	CE, EMC Class A
Contrast Ratio	2000:1	Control Method	WIFI
Brightness	1200 nits(cd/m <sup>2</sup> )	Installation Method	standby
Weight	35 kg / 77.16 lbs	Application Area	show,shopping mall, shop,reception, etc.

**Call us for details:**

#### Main Office:

722-8843 • 725-5424 • 724-7813  
 721-4332 • 725-0437 • 727-0637  
 721-6145 • 725-9359 • 722-8845

**Showroom:**  
 3rd Flr. V-Mall Shopping Ctr, Greenhills, San Juan City  
**The Brain Audiovisual Co.**  
 5th Flr. Bldg B, SM Megamall, Mandaluyong City

**AV SALES  
 RENTALS • DESIGN  
 SYSTEM  
 INTEGRATION**