



LED Poster

INDOOR

EYETOUCH

Features:

- Compact integration, multiple installation.
- Plug & play operation.
- Wireless fidelity connection, mobile app control (Android & IOS).
- Surface protective cover design, not reflective.
- Live editing, upload and show.
- Cluster control technology.
- Ultra light & thin.
- CE, ETL approval.



Specification:

Model	EYE TOUCH	Refresh Rate	1200-1920 Hz
Dimensions(WxHxD)	500x1926x56 mm / 19.69x75.83x2.20 inch	Best Viewing Distance	3~ 10m
Pixel Pitch	2.9mm / 0.11 inch	Viewing Angle(Horizontal)	130 (-65 ~ +65)°
Pixel Configuration	3 Chips in 1 SMD LED	Viewing Angle(Vertical)	130 (-65~ +65)°
Pixel Density	113,462 pixels/m ²	Serviceability	Rear
Resolution(WxH)	160x640	Input Voltage	AC110-240V, 50 & 60Hz
Aspect ratio	1:4	Certifications	CE, ETL
Contrast Ratio	2000:1	Control Method	WIFI
Brightness	1200 nits(cd/m ²)	Installation Method	standby, hung, wall mount, window design
Weight	25 kg / 55.12 lbs	Application Area	show, shopping mall, shop, reception, etc.

Call us for details:

Main Office:

8722-8843 • 8725-5424 • 8724-7813
8721-4332 • 8725-0437 • 8727-0637
8721-6145 • 8725-9359 • 8722-8845

Showroom:
3rd Flr. V-Mall Shopping Ctr, Greenhills, San Juan City
The Brain Audiovisual Co.
5th Flr. Bldg B, SM Megamall, Mandaluyong City.

**AV SALES
RENTALS • DESIGN
SYSTEM
INTEGRATION**

